

Beam

Beam takes the classic downlight to another level of direct lighting with a great light and wide range.

Orientable and adjustable, Beam can respond to every need for general and detail lighting. Now available with a square frame, XL size and asymmetrical versions.



Beam

Body

Aluminium body and heat sink. Aluminium trim attached by traction, with electrostatic 100% polyester paint finish. Available in fixed and adjustable versions (oriented by 30° horizontal rotation and 355° vertical rotation).

Light source

COB LED light source with excellent colour consistency (3 step-MacAdam) and long lifespan (>50.000h; L80/B10).

Accessories


Trimless version with recessing accessories supplied separately.

Diffuser

Diffused beam version supplied with prismatic acrylic diffuser (IP54). Acrylic diffuser for non-diffuse beam versions supplied separately (available only for fixed versions). This accessory allows an increase of the protection level up to IP54 (on the visible body).



Beam



.01 White



.01 White



.02 Black



.02 Black




.32 White + Black




.31 Black + White


Beam Q




.01 White



.02 Black





.32 White + Black




.31 Black + White

Adjustable


The beam of the luminaire can be oriented by 30° horizontal rotation and 355° vertical rotation.




Spot




Medium




Flood



Wide flood



Diffuse



Asymmetric

Beam


Beam

Beam Asymmetric

XL Fixed	Trim Ø200mm / Trimless Ø190mm			
L Fixed Adjustable	Trim Ø150mm / Trimless Ø140mm			
M Fixed Adjustable	Trim Ø110mm / Trimless Ø100mm		Trim Ø110mm	
S Fixed Adjustable	Trim Ø90mm / Trimless Ø75mm			
Accessory		Accessory IP54 Clear diffuser (for fixed versions)		




Adjustable

The beam of the luminaire can be oriented by 30° horizontal rotation and 355° vertical rotation.



Beam Q

Beam Q Asymmetric

	2700K	3000K	4000K
Trim Ø200mm	33W / 3000lm	33W / 3800lm	33W / 3950lm
			
Trim Ø150mm	17W / 1500lm	17W / 1900lm	17W / 2000lm
			
Trim Ø110mm	9W / 850lm	9W / 1050lm	9W / 1150lm
			
Trim Ø110mm	9W / 850lm	9W / 1050lm	9W / 1150lm
			
Trim Ø90mm	6W / 600lm	6W / 700lm	6W / 750lm
			
	Accessory IP54 Clear diffuser (for fixed versions)		