




Design: O/M  
Deckeneinbauleuchte aus Aluminium-Druckguss.  
Einbausystem mit Federklemmen.

LED CRI>90 / >50.000h, L80/B10 / 3-step MacAdam  
Driver separat zu bestellen.  
IP65 | 200mA / 100mA



 LED	3000K	Lichtquelle	Leuchte
Leistung	6,7W / 3,4W		6,7W / 3,4W
Strom	1055lm / 530lm		800lm / 400lm
Effizienz	157lm/W		119lm/W
LOR	-		76%
UGR	-		<16




Abstrahlwinkel  
Medium 34°

Anwendung



Gewicht  
0.21Kg



- Obligatorisch

**59101 Driver On/Off [200mA]**

147x43x30mm

**59100 Driver On/Off [100mA]**

110x40x21mm

**59103 Driver DALI [200mA]**

144x30x21mm

**59102 Driver DALI [100mA]**

144x30x21mm

### 59105 Driver PhaseCut [180mA]

102x49x29mm

### 59104 Driver PhaseCut [100mA]

122x41x23mm

**59107 Driver 1-10V [200mA]**

130x30x20mm

**59106 Driver 1-10V [120mA]**

130x30x20mm

## Daten gemäß Verordnungen

2019/2020/EU ergänzt durch 2021/341 | 2019/2015/EU ergänzt durch  
die Verordnung 2021/340/EU Energieverbrauchskennzeichnung.

Dieses Produkt enthält eine Lichtquelle der Effizienzklasse E  
Modellkennung BXRE-30G10FB-C-83