



Design: O/M + Bartenbach GmbH
Ceiling-recessed luminaire with aluminium die-cast body with electrostatic 100% polyester paint finish. Focal-lens with complex surfaces to provide a focal point through an 8mm aperture for low glare illumination.
Supplied with fermacell® plasterboard fiber recessing accessory or plasterboard.
Driver to be ordered separately.

LED CRI>90 / >50.000h, L80/B10
2-step MacAdam
IP65




 2700K	Light Source	Luminaire
Power	5,6W	5,6W
Flux	460lm	240lm
Efficiency	82lm/W	43lm/W
LOR	-	52%
UGR	-	<19



Beam angle
Medium 35°

Application



Weight
0,96Kg



● .02 Black / RAL 9005

59009 Driver On/Off [1 to 3 luminaire]
146,5x43,5x30mm

59010 Driver On/Off [3 to 6 luminaires]
115,5x76x30mm

59011 Driver DALI [1 luminaire]
95x53x30mm

59012 Driver DALI [up to 4 luminaires]
124x78x22mm

59013 Ceiling access hatch for drivers
365x365x13mm

59034 Plasterboard metal profile for Nub
250x47x18mm

59001 1/4 CTO
ø17x1mm

59002 1/2 CTO
ø17x1mm

59003 Louvre
ø17x3mm

59004 Soft diff
ø17x1mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class G
Model Identifier 4053560138