



Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Accurate reflector for a defined and controlled beam of light, achieving maximum efficiency.

Fitting accessories for different applications are available.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



LED	2700K	Light Source	Luminaire
Power		4,5W	5,8W
Flux		480lm	400lm
Efficiency		107lm/W	69lm/W
LOR		-	83%
UGR		-	-



Beam angle  
Asymmetric


Application



Weight  
0,39Kg



Ø75 (trim version)



Finishes


- .01 White / RAL 9010
- .02 Black / RAL 9005

Optional

- 59014** Accessory 12,5mm ceilings (flush installation)  
150x91x20mm
- 59038** Accessory 10-40mm ceilings (acoustic ceiling)  
156x100x78mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

Data according to regulations  
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class F  
Model Identifier 4053560098L



## One Asymmetric

Accessory 12,5mm ceilings  
(flush installation)

59014

Ø91




One accessory for flush version in  
false ceilings.  
For 12.5mm ceilings.

Weight  
**0,01Kg**


Finishes  
○ .01 White / RAL 9010

## One Asymmetric



**Recessing accessory for  
One. For 10 up to 40mm  
ceilings.**

**59038**



Recessing accessory for One.  
For 10 up to 40mm ceilings.

Weight  
**0,01Kg**

Finishes  
○ .01 White / RAL 9010  
● .02 Black / RAL 9005