

Design: O/M + Bartenbach GmbH
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.
Accurate reflector for a defined and controlled beam of light, achieving maximum efficiency.
Fitting accessories for different applications are available.

LED CRI>90 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



| LED | 3000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 9,8W | 12,3W |
| Flux | | 1035lm | 880lm |
| Efficiency | | 106lm/W | 72lm/W |
| LOR | | - | 85% |
| UGR | | - | - |




Beam angle
Asymmetric

Application

Weight
0,39Kg



Ø75 (trim version)



Finishes

○ .01 White / RAL 9010
● .02 Black / RAL 9005

Optional

59014 Accessory 12,5mm ceilings (flush installation)
150x91x20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling)
156x100x78mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 |2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier 4053560099H