



Design: O/M + Bartenbach GmbH  
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.  
Lightcore optics for defined and perfectly controlled beam of light.  
Easy recessing system with spring clips.  
Fitting accessories for different applications are available.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included. DALI DT8  
IP20 | 230Vac | 50/60Hz



| LED        | 2200K-5000K | Light Source | Luminaire |
|------------|-------------|--------------|-----------|
| Power      |             | 5,6W*        | 7W*       |
| Flux       |             | 460lm*       | 380lm*    |
| Efficiency |             | 82lm/W       | 54lm/W    |
| LOR        |             | -            | 83%       |
| UGR        |             | -            | <16       |



Beam angle  
Flood 56°

Application

Weight  
0.53



Ø78 (trim version)



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Optional

- 59014** Accessory 12,5mm ceilings (flush installation)  
150x91x20mm
- 59038** Accessory 10-40mm ceilings (acoustic ceiling)  
156x100x78mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com