

9,8W / 1110lm / 4000K / On/Off / Flood 56° /
ø85mm

60219



Design: O/M + Bartenbach GmbH

Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Lightcore optics for defined and perfectly controlled beam of light.

Easy recessing system with spring clips.

Fitting accessories for different applications are available.

LED CRI>80 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP65 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		9,8W	12,3W
Flux		1360lm	1110lm
Efficiency		139lm/W	91lm/W
LOR		-	82%
UGR		-	<19



Beam angle
Flood 56°

Application



Weight
0,53Kg



Ø78 (trim version)



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Optional


59014 Accessory 12,5mm ceilings (flush installation)
150x91x20mm

59038 Accessory 10-40mm ceilings (acoustic ceiling)
156x100x78mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F Model Identifier 2053560247H



**Accessory 12,5mm ceilings
(flush installation)**

59014



One accessory for flush version in
false ceilings.
For 12.5mm ceilings.

Weight
0,01Kg

Finishes
○ .01 White / RAL 9010



**Recessing accessory for
One. For 10 up to 40mm
ceilings.**

59038



Recessing accessory for One.
For 10 up to 40mm ceilings.

Weight
0,01Kg

Finishes
○ .01 White / RAL 9010
● .02 Black / RAL 9005