

9,8W / 700lm / 2700K / DALI / Medium 41° /  
ø85mm

60249



Design: O/M + Bartenbach GmbH

Surface spotlight with die-cast aluminium body with electrostatic 100% polyester paint finish.


Spot-lens with individual complex surface ribs to provide a focal light and an extremely narrow beam. Orientable by 90° horizontal rotation and 330° vertical rotation.

Driver included.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Driver included.  
IP20 | 230Vac | 50/60Hz




| LED                 | 2700K | Light Source | Luminaire |
|---------------------|-------|--------------|-----------|
| Power               |       | 9,8W         | 12,3W     |
| Flux                |       | 955lm        | 700lm     |
| Efficiency          |       | 97lm/W       | 57lm/W    |
| LOR                 |       | -            | 73%       |
| Operating Condition |       | -            | 230Vac    |



Beam angle  
Medium 41°

Application

Weight  
0,64Kg



### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F  
Model Identifier 2053560245H