

4,5W / 470lm / 3000K / DALI / Flood 59° /  
ø85mm

60258



Design: O/M + Bartenbach GmbH  
Surface spotlight with die-cast aluminium body with electrostatic 100% polyester paint finish.  
Spot-lens with individual complex surface ribs to provide a focal light and an extremely narrow beam.  
Orientable by 90° horizontal rotation and 330° vertical rotation.  
Driver included.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



| LED 3000K           | Light Source | Luminaire |
|---------------------|--------------|-----------|
| Power               | 4,5W         | 5,8W      |
| Flux                | 520lm        | 470lm     |
| Efficiency          | 116lm/W      | 81lm/W    |
| LOR                 | -            | 90%       |
| Operating Condition | -            | 230Vac    |



Beam angle  
Flood 59°

Application

Weight  
0,64Kg



### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Data according to regulations  
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class F  
Model Identifier 2053560257L