

9,8W / 700lm / 2700K / On/Off / Medium 41°  
/ ø85mm

60269



Design: O/M + Bartenbach GmbH  
Track-mounted spotlight with die-cast aluminium body with electrostatic 100% polyester paint finish. Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam. Orientable by 90° horizontal rotation and 330° vertical rotation.  
Driver included.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Driver included.  
IP20 | 230Vac | 50/60Hz



| LED                 | 2700K | Light Source | Luminaire |
|---------------------|-------|--------------|-----------|
| Power               |       | 9,8W         | 12,3W     |
| Flux                |       | 955lm        | 700lm     |
| Efficiency          |       | 97lm/W       | 57lm/W    |
| LOR                 |       | -            | 73%       |
| Operating Condition |       | -            | 230Vac    |



Beam angle  
Medium 41°

Application

Weight  
0,64Kg



### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Data according to regulations  
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F  
Model Identifier 2053560245H