

O/M

Onit Track (230v)

10W / 990lm / 4000K / On/Off / Medium 28°
/ ø45mm

60325

Design: O/M

Adjustable spotlight with aluminium body for installation on three-phase track.

The spotlight can be rotated up to 90° horizontally and 330° vertically.

Accessories available separately and easily applicable after installation.

LED CRI>80 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



LED 4000K	Light Source	Luminaire
Power	10W	12,5W
Flux	1240lm	990lm
Efficiency	136lm/W	79lm/W
LOR	-	0.73
UGR	-	<16



Beam angle
Medium 28°

Application



Weight
0,6Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Optional

59016 Elliptical refractor

Ø39x0,5mm

59017 Soft diffuser

Ø39x0,5mm

59018 Louvre

Ø39x3mm

59019 Snoot 72mm

Ø45x72

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F
Model Identifier 2053560247H