




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz




 3000K	Light Source	Luminaire
Power	10W	12,5W
Flux	1035lm	760lm
Efficiency	104lm/W	61lm/W
LOR	-	73%
UGR	-	<19




Beam angle  
Medium 23°

Application



Weight  
0,38Kg

 Ø70 (trim version)



- Finishes
- .04 Matt White
  - .05 Matt Black

- Optional
- 59063 Flush accessory (12.5mm ceilings)  
176x17mm
  - 59064 Flush accessory (15mm ceilings)  
176x19,5mm
  - 59065 Flush accessory (25mm ceilings)  
176x29,5mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com  
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations  
2019/2020/EU supplemented by 2021/341 |2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class F  
Model Identifier 2053560257H