





Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing accessory for flush version supplied separately.


LED CRI>90 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



 3000K	Light Source	Luminaire
Power	10W	12,5W
Flux	1035lm	780lm
Efficiency	104lm/W	62lm/W
LOR	-	75%
UGR	-	<22




Beam angle
Flood 37°

Application


Weight
0,38Kg



Ø70 (trim version)



- Finishes**
- .04 Matt White
 - .05 Matt Black

- Optional**
- 59063** Flush accessory (12.5mm ceilings)
176x17mm
 - 59064** Flush accessory (15mm ceilings)
176x19,5mm
 - 59065** Flush accessory (25mm ceilings)
176x29,5mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F
Model Identifier 2053560257H