





Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing accessory for flush version supplied separately.

LED CRI>80 / >50.000h, L80/B10  
2-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



 <b>4000K</b>	<b>Light Source</b>	<b>Luminaire</b>
<b>Power</b>	<b>10W</b>	<b>12,5W</b>
<b>Flux</b>	<b>1240lm</b>	<b>940lm</b>
<b>Efficiency</b>	<b>124lm/W</b>	<b>75lm/W</b>
<b>LOR</b>	<b>-</b>	<b>76%</b>
<b>UGR</b>	<b>-</b>	<b>&lt;22</b>



<b>Beam angle</b> <b>Flood 37°</b>
<b>Application</b> 
<b>Weight</b> <b>0,38Kg</b>



Ø70 (trim version)



- Finishes
- .04 Matt White
  - .05 Matt Black

- Optional
- 59063** Flush accessory (12.5mm ceilings)  
176x17mm
  - 59064** Flush accessory (15mm ceilings)  
176x19,5mm
  - 59065** Flush accessory (25mm ceilings)  
176x29,5mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com  
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations  
2019/2020/EU supplemented by 2021/341 |2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class F  
Model Identifier 2053560247H