



Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



LED	2700K	Light Source	Luminaire
Power	10W	12,5W	
Flux	1100lm	820lm	
Efficiency	110lm/W	66lm/W	
LOR	-	75%	
UGR	-	<19	



Beam angle
Medium 28°

Application

Weight
0,5Kg



Ø95 (trim version)



- Finishes
- .04 Matt White
 - .05 Matt Black

Optional

59066 Flush accessory (12.5mm ceilings)
201x17mm

59067 Flush accessory (15mm ceilings)
201x19,5mm

59068 Flush accessory (25mm ceilings)
201x29,5mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F

Model Identifier BXR-27G2000-C-73