





Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



 2700K	Light Source	Luminaire
Power	10W	12,5W
Flux	1100lm	870lm
Efficiency	110lm/W	70lm/W
LOR	-	79%
UGR	-	<22



Beam angle Flood 46°
Application 
Weight 0,5Kg



Ø95 (trim version)



- Finishes
- .04 Matt White
 - .05 Matt Black

Optional
59066 Flush accessory (12.5mm ceilings)
201x17mm
59067 Flush accessory (15mm ceilings)
201x19,5mm
59068 Flush accessory (25mm ceilings)
201x29,5mm
For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 |2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier BXRc-27G2000-C-73