

Beam

10W / 900lm / 3000K / On/Off / Medium 28°
/ ø100mm


60368



Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing accessory for flush version supplied separately.


LED CRI>80 / >50.000h, L80/B10
3-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



| | | |
|--|---------------------|------------------|
|  3000K | Light Source | Luminaire |
| Power | 10W | 12,5W |
| Flux | 1200lm | 900lm |
| Efficiency | 120lm/W | 72lm/W |
| LOR | - | 75% |
| UGR | - | <19 |




Beam angle
Medium 28°

Application


Weight
0,5Kg



Ø95 (trim version)



- Finishes
- .04 Matt White
 - .05 Matt Black

- Optional
- 59066** Flush accessory (12.5mm ceilings)
201x17mm
 - 59067** Flush accessory (15mm ceilings)
201x19,5mm
 - 59068** Flush accessory (25mm ceilings)
201x29,5mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class E
Model Identifier BXR-30E2000-C-73