

19W / 1640lm / 3000K / On/Off / Medium  
28° / ø100mm

60369



Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing accessory for flush version supplied separately.

LED CRI>80 / >50.000h, L80/B10  
3-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz




| LED        | 3000K   | Light Source | Luminaire |
|------------|---------|--------------|-----------|
| Power      | 19W     | 23,2W        |           |
| Flux       | 2180lm  | 1640lm       |           |
| Efficiency | 115lm/W | 71lm/W       |           |
| LOR        | -       | 75%          |           |
| UGR        | -       | <22          |           |



Beam angle  
Medium 28°

Application

Weight  
0,5Kg



Finishes

- .04 Matt White
- .05 Matt Black

Optional

- 59066** Flush accessory (12.5mm ceilings)  
201x17mm
- 59067** Flush accessory (15mm ceilings)  
201x19,5mm
- 59068** Flush accessory (25mm ceilings)  
201x29,5mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations  
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class E  
Model Identifier BXR-30E2000-C-73