

## Beam

10W / 950lm / 3000K / On/Off / Flood 46° /  
ø100mm

60370




Design: O/M


Ceiling-recessed luminaire made of aluminium die-cast.

Recessing accessory for flush version supplied separately.

LED CRI>80 / >50.000h, L80/B10  
3-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



 LED	3000K	Light Source	Luminaire
Power		10W	12,5W
Flux		1200lm	950lm
Efficiency		120lm/W	76lm/W
LOR		-	79%
UGR		-	<22



Beam angle  
Flood 46°


## Application



Weight  
0,5Kg



Ø95 (trim version)



## Finishes

- .04 Matt White  
● .05 Matt Black

## Optional

**59066 Flush accessory (12.5mm ceilings)**

201x17mm

**59067 Flush accessory (15mm ceilings)**

201x19,5mm

**59068 Flush accessory (25mm ceilings)**

201x29,5mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class E  
Model Identifier BXRC-30E2000-C-73