

19W / 1720lm / 3000K / On/Off / Flood 46° /
ø100mm

60371



Design: O/M


Ceiling-recessed luminaire made of aluminium die-cast.

Recessing accessory for flush version supplied separately.


LED CRI>80 / >50.000h, L80/B10
3-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power	19W	23,2W	
Flux	2180lm	1720lm	
Efficiency	115lm/W	74lm/W	
LOR	-	79%	
UGR	-	<22	



Beam angle Flood 46°
Application
Weight 0,5Kg



- Finishes
- .04 Matt White
 - .05 Matt Black

- Optional
- 59066 Flush accessory (12.5mm ceilings)
201x17mm
 - 59067 Flush accessory (15mm ceilings)
201x19,5mm
 - 59068 Flush accessory (25mm ceilings)
201x29,5mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class E
Model Identifier BXR-30E2000-C-73