




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing accessory for flush version supplied separately.

LED CRI>80 / >50.000h, L80/B10  
3-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



 <b>3000K</b>	<b>Light Source</b>	<b>Luminaire</b>
<b>Power</b>	<b>10W</b>	<b>12,5W</b>
<b>Flux</b>	<b>1200lm</b>	<b>950lm</b>
<b>Efficiency</b>	<b>120lm/W</b>	<b>76lm/W</b>
<b>LOR</b>	<b>-</b>	<b>79%</b>
<b>UGR</b>	<b>-</b>	<b>&lt;22</b>



<b>Beam angle</b> <b>Flood 46°</b>
<b>Application</b> 
<b>Weight</b> <b>0,5Kg</b>



Ø95 (trim version)



- Finishes
- .04 Matt White
  - .05 Matt Black

- Optional
- 59066** Flush accessory (12.5mm ceilings)  
201x17mm
  - 59067** Flush accessory (15mm ceilings)  
201x19,5mm
  - 59068** Flush accessory (25mm ceilings)  
201x29,5mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com  
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations  
2019/2020/EU supplemented by 2021/341 |2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class E  
Model Identifier BXR-30E2000-C-73