



Design: O/M

Ceiling-recessed luminaire made of aluminium die-cast.

Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10
2-step MacAdam / power supply included
IP54 | 230Vac | 50/60Hz




LED	2700K	Light Source	Luminaire
Power		10W	12,5W
Flux		955lm	700lm
Efficiency		96lm/W	56lm/W
LOR		-	73%
UGR		-	<22



Beam angle Flood 37°
Application
Weight 0,38Kg



Ø70 (trim version)



Finishes

- .04 Matt White
- .05 Matt Black

Optional

- 59063** Flush accessory (12.5mm ceilings)
176x17mm
- 59064** Flush accessory (15mm ceilings)
176x19,5mm
- 59065** Flush accessory (25mm ceilings)
176x29,5mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier 2053560245H

Beam IP54

Flush accessory (12.5mm
ceilings)

59063



Ø88



Flush accessory Beam ø75
For 12.5mm ceilings.

Weight
0,05Kg

Finishes
.99


Beam IP54

Flush accessory (15mm
ceilings)

59064



Ø88



Flush accessory Beam ø75
For 15mm ceilings.

Weight
0,05Kg

Finishes
.99

Beam IP54

Flush accessory (25mm
ceilings)

59065



Ø88



Flush accessory Beam Ø75
For 25mm ceilings.

Weight
0,05Kg

Finishes
.99