



Design: O/M


Ceiling-recessed luminaire made of aluminium die-cast.

Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / power supply included  
IP54 | 230Vac | 50/60Hz




LED	2700K	Light Source	Luminaire
Power		10W	12,5W
Flux		955lm	520lm
Efficiency		96lm/W	42lm/W
LOR		-	54%
UGR		-	<28



Beam angle	105°
Diffuse	
Application	
Weight	0,38Kg



Ø70 (trim version)



### Finishes

- .04 Matt White
- .05 Matt Black

### Optional

- 59063** Flush accessory (12.5mm ceilings)  
176x17mm
- 59064** Flush accessory (15mm ceilings)  
176x19,5mm
- 59065** Flush accessory (25mm ceilings)  
176x29,5mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com  
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations  
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class F  
Model Identifier 2053560245H


## Beam IP54

Flush accessory (12.5mm  
ceilings)

59063



Ø88



Flush accessory Beam Ø75  
For 12.5mm ceilings.

Weight  
0,05Kg

Finishes  
.99


## Beam IP54

Flush accessory (15mm  
ceilings)

59064



Ø88



Flush accessory Beam ø75  
For 15mm ceilings.

Weight  
0,05Kg

Finishes  
.99


## Beam IP54

Flush accessory (25mm  
ceilings)

59065



Ø88



Flush accessory Beam ø75  
For 25mm ceilings.

Weight  
0,05Kg

Finishes  
.99