

Beam
IP5419W / 1620lm / 4000K / On/Off / Diffuse /
ø100mm

60463



Design: O/M

Ceiling-recessed luminaire made of aluminium die-cast.

Recessing accessory for flush version supplied separately.

LED CRI>80 / >50.000h, L80/B10
3-step MacAdam / power supply included
IP54 | 230Vac | 50/60Hz

LED	4000K	Light Source	Luminaire
Power		19W	23,2W
Flux		2740lm	1620lm
Efficiency		144lm/W	70lm/W
LOR		-	59%
UGR		-	<28

Beam angle
Diffuse

Application

Weight
0,5Kg

Ø95 (trim version)



Finishes

- .04 Matt White
- .05 Matt Black

Optional

- 59066** Flush accessory (12.5mm ceilings)
201x17mm
- 59067** Flush accessory (15mm ceilings)
201x19,5mm
- 59068** Flush accessory (25mm ceilings)
201x29,5mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class E
Model Identifier BXR-40E2000-C-78

Beam IP54

Flush accessory (12.5mm
ceilings)

59066



Ø112



Flush accessory Beam ø100
For 12.5mm ceilings.

Weight
0,05Kg

Finishes
.99



Beam IP54

Flush accessory (15mm
ceilings)

59067




Ø112



Flush accessory Beam Ø100
For 15mm ceilings.

Weight
0,05Kg

Finishes
.99



Beam IP54

Flush accessory (25mm
ceilings)

59068



Ø112



Flush accessory Beam Ø100
For 25mm ceilings.

Weight
0,05Kg

Finishes
.99

