



Design: O/M


Ceiling-recessed luminaire made of aluminium die-cast.

Recessing accessory for flush version supplied separately.

LED CRI>80 / >50.000h, L80/B10  
3-step MacAdam / power supply included  
IP54 | 230Vac | 50/60Hz





LED	4000K	Light Source	Luminaire
Power		19W	23,2W
Flux		2740lm	1620lm
Efficiency		144lm/W	70lm/W
LOR		-	59%
UGR		-	<28



Beam angle	105°
Diffuse	
Application	
Weight	0,5Kg



Ø95 (trim version)



### Finishes

- .04 Matt White
- .05 Matt Black

### Optional

- 59066** Flush accessory (12.5mm ceilings)  
201x17mm
- 59067** Flush accessory (15mm ceilings)  
201x19,5mm
- 59068** Flush accessory (25mm ceilings)  
201x29,5mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com  
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations  
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class E  
Model Identifier BXR-40E2000-C-90