



Design: O/M

Ceiling-recessed luminaire, with aluminium body with 25micron maximum corrosion resistance anodization. Trim aluminium with matt finish or with textured electrostatic 100% polyester paint.

Tempered clear glass.

Supplied with cable (2x0,50mm²).

Driver to be ordered separately.


Values for 700mA. For 350mA estimate half of the indicated values.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

IP67 | 350mA / 700mA




| LED | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 2,2W | 2,2W |
| Flux | | 305lm | 260lm |
| Efficiency | | 139lm/W | 118lm/W |
| LOR | | - | 85% |
| UGR | | - | <19 |



Beam angle
Medium 21°

Application



Weight
0,07Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .12 Brushed stainless steel
- .34 Rust

Mandatory

- 59124** 15W Driver
1 to 10 luminaires / 350mA
- 59125** 8W Driver
1 to 5 luminaires / 350mA
- 59126** 15W Driver
1 to 10 luminaires / 350mA
- 59127** 25W Driver
5 to 18 luminaires / 350mA
- 59128** 11W Driver
1 to 4 luminaires / 700mA
- 59129** 35W Driver
1 to 12 luminaires / 700mA
- 59130** 17W Driver
1 to 5 luminaires / 700mA
- 59131** 48W Driver
1 to 18 luminaires / 700mA

Optional

- 27400** IP68 Connector 2 way
4 poles
- 27395** IP68 Pass-through wiring connection box
3 way