

43W / 4800lm / 4000K / DALI / Wide flood  
76° / 2353mm

60526

Product timing available by request



Design: OM + Bartenbach GmbH  
Surface or pendant luminaire with housing made of aluminium with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish. Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured finish.


Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.

Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



| LED        | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 43W          | 49,9W     |
| Flux       |       | 6000lm       | 4800lm    |
| Efficiency |       | 142lm/W      | 96lm/W    |
| LOR        |       | -            | 80%       |
| UGR        |       | -            | <19       |



Beam angle  
Wide flood 76°

Application



Weight  
3,8Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com