

27+56W / 2720+2560lm / 3000K / DALI /
Flood 64° / batwing / 2344mm

60534

Product timing available by request



Design: OM + Bartenbach GmbH
Pendant direct and indirect luminaire with housing made of aluminium in matte finish.
Aluminium anodised end caps with matt finish.
Linear lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.
Indirect light: Lenses for batwing effect protected by a transparent polycarbonate diffuser.
Fitting accessories ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



| LED | 3000K | Light Source | Luminaire |
|------------|-------|--------------|-------------|
| Power | | 27+56W | 32+64W |
| Flux | | 3360+3200lm | 2720+2560lm |
| Efficiency | | 79lm/W | 53lm/W |
| LOR | | - | 80% |
| UGR | | - | <13 |



Beam angle
Flood 64° /
batwing

Application



Weight
8,2Kg



Finishes

- .04 Matt White
- .05 Matt Black

Mandatory

59054 Pendant direct/indirect fitting accessory

56051 Clear Base DALI

ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com