

56W* / 6000lm* / 2200K-5000K / DALI /
Wide flood 76° / 2933mm

60553

Product timing available by request

Design: OM + Bartenbach GmbH

Recessed luminaire with housing made of aluminium with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Linear extruded lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 2-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



LED	2200K-5000K	Light Source	Luminaire
Power	56W*		65,9W*
Flux	7500lm*		6000lm*
Efficiency	134lm/W		91lm/W
LOR	-		80%
UGR	-		<19



Beam angle
Wide flood 76°


Application



Weight
4,7Kg



47x2923



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory
51027 Recessed fitting accessory

O/M recommends that any false ceilings intended for recessed products should be installed only after the products to be used have been chosen. The same applies when preparing openings for this type of product. O/M recommends reinforcing false ceilings close to any such openings, in accordance with the characteristics of the product to be recessed. The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com