

28W\* / 3000lm\* / 2200K-5000K / DALI /  
Flood 64° / 1489mm

60556

Product timing available by request



Design: OM + Bartenbach GmbH

Surface or pendant luminaire with housing made of aluminium with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Linear extruded lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 2-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



| LED        | 2200K-5000K | Light Source | Luminaire |
|------------|-------------|--------------|-----------|
| Power      |             | 28W*         | 34,1W*    |
| Flux       |             | 3750lm*      | 3000lm*   |
| Efficiency |             | 134lm/W      | 88lm/W    |
| LOR        |             | -            | 80%       |
| UGR        |             | -            | <13       |



Beam angle  
Flood 64°

Application



Weight  
2,4Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm