

8W\* / 390lm\* / 2200K-5000K / DALI /  
Wallwasher / 611mm

60600



Design: OM + Bartenbach GmbH

Surface or pendant luminaire with housing made of aluminium with 25 micron maximum corrosion resistance anodization in matte finish or electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Linear extruded lenses (Lightstream) combined with a secondary reflector, integrated into an extruded aluminium profile.

Fitting accessories ordered separately. 2200-5000K Tunable White.

LED CRI&gt;80 / &gt;50.000h, L80/B10 / 2-step MacAdam


Power supply included.

DALI DT8


IP20 | 230Vac | 50/60Hz



LED	2200K-5000K	Light Source	Luminaire
Power		8W*	10W*
Flux		860lm*	390lm*
Efficiency		108lm/W	39lm/W
LOR		-	45%
UGR		-	-

Beam angle  
Wallwasher

Application

Weight  
1,64Kg

## Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

## Mandatory

54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm

