

26W / 1960lm / 3000K / On/Off / Flood 52° /  
611mm

60669



Design: O/M + Bartenbach GmbH

Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision35 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source.

Fitting accessories for pendant version ordered separately.

LED CRI&gt;90 / &gt;50.000h, L80/B10 / 2-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



| LED 3000K  | Light Source | Luminaire |
|------------|--------------|-----------|
| Power      | 26W          | 31,7W     |
| Flux       | 2580lm       | 1960lm    |
| Efficiency | 99lm/W       | 62lm/W    |
| LOR        | -            | 76%       |
| UGR        | -            | <16       |

Beam angle  
Flood 52°

Application

Weight  
1,2Kg

Finishes

○ .01 White / RAL 9010

● .02 Black / RAL 9005

Mandatory

54036 Pendant direct fitting accessory

54034 Clear Base

ø60x35mm

