

23W\* / 1420lm\* / 2200K-5000K / DALI /  
 Flood 52° / 611mm

**60703**


Design: O/M + Bartenbach GmbH


Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision35 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source.


Fitting accessories for pendant version ordered separately.

LED >80CRI<90 / >50.000h, L80/B10 / 3-step MacAdam  
 Power supply included.  
 DALI DT8.  
 IP20 | 230Vac | 50/60Hz



Beam angle  
 Flood 52°

Application



Weight  
 1,2Kg

LED	2200K-5000K	Light Source	Luminaire
Power		23W*	29W*
Flux		1880lm*	1420lm*
Efficiency		82lm/W	49lm/W
LOR		-	76%
UGR		-	<16



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

**54036** Pendant direct fitting accessory

**56051** Clear Base DALI

ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)