

# U35

## Surface/Pendant

54W / 5000lm / 3000K / DALI / Diffuse /  
2271mm

60831



Design: Eduardo Souto de Moura

Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint. Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP40 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power		54W	63,5W
Flux		9800lm	5000lm
Efficiency		181lm/W	79lm/W
LOR		-	51%
UGR		-	<28



Beam angle  
Diffuse

Application



Weight  
2,7Kg



### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

### Mandatory

54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603216

## U35 Surface/Pendant

Pendant direct fitting  
accessory

54036



One 2m steel cable (1,2mm)  
Max interval 3m

## U35 Surface/Pendant

Clear Base DALI

56051



DALI (5x0,75mm<sup>2</sup>). Includes:  
 One clear polycarbonate power supply base (IP20).  
 One clear power cable (2m).  
 One clear power supply base must be applied every 30m (Ø60x35mm)  
 Steel cable ordered separately