

## U35

### Made-to-measure

41W / 3750lm / 3000K / On/Off / Diffuse /  
1679mm

60891

Design: O/M

LED light source with good colour consistency and  
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



#### Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

#### Diffuser

- A Polycarbonate frost  
diffuser

#### Light Source

- B LED Modules

| LED        | 3000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 41W          | 48,2W     |
| Flux       |       | 7350lm       | 3750lm    |
| Efficiency |       | 179lm/W      | 78lm/W    |
| LOR        |       | -            | 51%       |
| UGR        |       | -            | <28       |




Beam angle  
Diffuse

Application



Weight  
0,6Kg



#### Finishes

Choose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: [support@om-light.com](mailto:support@om-light.com)

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603216