

8,9W / 865lm / 4000K / DALI / Diffuse /  
629mm

60922

Design: O/M

LED light source with good colour consistency and  
long operation lifespan.LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz**Structure**

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

**Diffuser**A Polycarbonate frost  
diffuser**Light Source**

B LED Modules

LED	4000K	Light Source	Luminaire
Power		8,9W	11,1W
Flux		1700lm	865lm
Efficiency		191lm/W	78lm/W
LOR		-	51%
UGR		-	<25

Beam angle  
Diffuse**Application**Weight  
0,5Kg**Finishes**For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)Choose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: [support@om-light.com](mailto:support@om-light.com)**Data according to regulations**2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603204, 89603217