

## U45

### Surface/Pendant

40W / 3350lm / 3000K / On/Off / Diffuse /  
2831mm

61121



Design: Eduardo Souto de Moura

Surface or pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with matt finish or with textured electrostatic 100% polyester paint. Frosted polycarbonate diffuser with user friendly clipping system and double fitting system: flushed or recessed.

Aluminium anodised end caps with matt finish or electrostatic 100% polyester paint with textured-finish.

Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP40 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power		40W	47,1W
Flux		7150lm	3350lm
Efficiency		179lm/W	71lm/W
LOR		-	47%
UGR		-	<25




Beam angle  
Diffuse

Application



Weight  
4,5Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .10 Anodised aluminium

Mandatory

**54036** Pendant direct fitting accessory

**54034** Clear Base

ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603211, 89603216