

20W / 2040lm / 3000K / DALI / Wide flood  
80° / 1747mm

61165

Compatibility with other modules must be confirmed  
with [support@om-light.com](mailto:support@om-light.com)

Design: OM + Bartenbach  
GmbH

Module with linear extruded lenses (Lightstream)  
combined with a secondary reflector, integrated into  
an extruded aluminium profile.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



| LED        | 3000K | Light Source | Luminaire          |
|------------|-------|--------------|--------------------|
| Power      |       | 20W          | 24W                |
| Flux       |       | 2520lm       | 2040lm             |
| Efficiency |       | 127lm/W      | 87lm/W             |
| LOR        |       | -            | 0.8100000000000001 |
| UGR        |       | -            | <19                |



Beam angle  
**Wide flood 80°**

Application

Weight



### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)

Choose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: [support@om-light.com](mailto:support@om-light.com)