


52W / 3760lm / 3000K / DALI / Medium 31° /  
1200mm

**61286**

**Structure**

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

**Modules**

- A inVision Module


Design: O/M + Bartenbach GmbH

inVision module with housing and perforated cover plate made of aluminium with textured-paint finish.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz


LED	3000K	Light Source	Luminaire
<b>Power</b>		<b>52W</b>	<b>61,2W</b>
<b>Flux</b>		<b>5160lm</b>	<b>3760lm</b>
<b>Efficiency</b>		<b>99lm/W</b>	<b>61lm/W</b>
<b>LOR</b>		-	<b>73%</b>
<b>UGR</b>		-	<b>&lt;13</b>


**Beam angle**  
**Medium 31°**
**Application**

**Weight**  
**0,8Kg**

**Finishes**

- .01 White / RAL 9010
- .02 Black / RAL 9005

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com