

46W\* / 2840lm\* / 2200K-5000K / On/Off /  
Flood 52° / 1200mm

61300

Design: O/M + Bartenbach GmbH  
inVision module with housing and perforated cover  
plate made of aluminium with textured-paint finish.  
2200-5000K Tunable White

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
DALI DT8.  
IP20 | 230Vac | 50/60Hz



#### Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

#### Modules

A inVision Module

| LED        | 2200K-5000K | Light Source | Luminaire |
|------------|-------------|--------------|-----------|
| Power      |             | 46W*         | 54,1W*    |
| Flux       |             | 3760lm*      | 2840lm*   |
| Efficiency |             | 82lm/W       | 52lm/W    |
| LOR        |             | -            | 76%       |
| UGR        |             | -            | <16       |



Beam angle  
Flood 52°

#### Application



Weight  
0,6Kg



#### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Choose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: [support@om-light.com](mailto:support@om-light.com)