

12W / 980lm / 2700K / DALI / Diffuse /
839mm

61324

Design: O/M
LED light source with good colour consistency and
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



- Structure**
 - 1 Profile
 - 2 End caps
 - 3 Fitting accessories
 - 4 Profile coupling
- Diffuser**
 - A Polycarbonate frost diffuser
- Light Source**
 - B LED Modules

| LED | 2700K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 12W | 14,6W |
| Flux | | 2100lm | 980lm |
| Efficiency | | 175lm/W | 67lm/W |
| LOR | | - | 47% |
| UGR | | - | <25 |



Beam angle
Diffuse

Application



Weight
0,51Kg



Finishes

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com
Choose the length and layout of the system exactly as you want it, to
model the right lighting functions for different tasks. For further
information please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class C
and D
Model Identifier 89603210, 89603215