

41W / 3660lm / 4000K / On/Off / Diffuse /  
1679mm

61379

Design: O/M  
LED light source with good colour consistency and  
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



- |                       |                                |
|-----------------------|--------------------------------|
| <b>Structure</b>      | <b>Diffuser</b>                |
| 1 Profile             | A Polycarbonate frost diffuser |
| 2 End caps            |                                |
| 3 Fitting accessories | <b>Light Source</b>            |
| 4 Profile coupling    | B LED Modules                  |

LED	4000K	Light Source	Luminaire
Power		41W	48,2W
Flux		7800lm	3660lm
Efficiency		190lm/W	76lm/W
LOR		-	47%
UGR		-	<25



Beam angle  
Diffuse

Application



Weight  
0,6Kg



#### Finishes

Choose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: [support@om-light.com](mailto:support@om-light.com)

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603217