

## U60 Made-to-measure

8,9W / 775lm / 3000K / On/Off / Diffuse /  
629mm

61930

Design: O/M

LED light source with good colour consistency and  
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



### Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

### Diffuser

- A Polycarbonate frost  
diffuser

### Light Source

- B LED Modules

| LED        | 3000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 8,9W         | 11,1W     |
| Flux       |       | 1610lm       | 775lm     |
| Efficiency |       | 181lm/W      | 70lm/W    |
| LOR        |       | -            | 48%       |
| UGR        |       | -            | <25       |



Beam angle  
Diffuse

Application



Weight  
0,5Kg



### Finishes

Choose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: [support@om-light.com](mailto:support@om-light.com)

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603203, 89603216

