

9,9W / 860lm / 3000K / DALI / Diffuse /
699mm

61948

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

Diffuser

- A Polycarbonate frost diffuser

Light Source

- B LED Modules

| LED | 3000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 9,9W | 12,4W |
| Flux | | 1790lm | 860lm |
| Efficiency | | 181lm/W | 69lm/W |
| LOR | | - | 48% |
| UGR | | - | <25 |



Beam angle
Diffuse

Application



Weight
0,5Kg



Finishes

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C
Model Identifier 89603206, 89603216

