

24W / 2175lm / 4000K / DALI + E-KIT /  
Diffuse / 1679mm

61990

Design: O/M

LED light source with good colour consistency and  
long operation lifespan.LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz

## Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

## Diffuser

A Polycarbonate frost  
diffuser

## Light Source

B LED Modules

LED	4000K	Light Source	Luminaire
Power		24W	29,3W
Flux		4530lm	2175lm
Efficiency		189lm/W	74lm/W
LOR		-	48%
UGR		-	<25

Beam angle  
Diffuse

## Application

Weight  
0,8Kg

## Finishes

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.comChoose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: support@om-light.com

## Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603217