


52W / 4350lm / 3000K / DALI / Diffuse /
857mm

62135

Design: O/M
LED light source with good colour consistency and
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



- Structure**

 - 1 Profile
 - 2 End caps
 - 3 Fitting accessories
 - 4 Profile coupling
- Diffuser**

 - A Polycarbonate frost diffuser
- Light Source**

 - B LED Modules

LED	3000K	Light Source	Luminaire
Power		52W	62,4W
Flux		7050lm	4350lm
Efficiency		133lm/W	70lm/W
LOR		-	62%
UGR		-	<25



Beam angle
Diffuse

Application


Weight
0,51Kg



Finishes

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

Choose the length and layout of the system exactly as you want it, to
model the right lighting functions for different tasks. For further
information please contact: support@om-light.com



Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class D
Model Identifier WU-M-526-S-BC-830, WU-M-536-S-BC-830