

U120 Made-to-measure

104W / 8700lm / 3000K / DALI + E-KIT /
Diffuse / 1715mm

62143

Design: O/M

LED light source with good colour consistency and long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

Diffuser

- A Polycarbonate frost diffuser

Light Source

- B LED Modules

| LED | 3000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 104W | 121W |
| Flux | | 14100lm | 8700lm |
| Efficiency | | 134lm/W | 72lm/W |
| LOR | | - | 62% |
| UGR | | - | <25 |



Beam angle
Diffuse

Application



Weight
0,8Kg



Finishes

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class D
Model Identifier WU-M-536-S-BC-830