

27+20W / 2440+1480lm / 4000K / On/Off /
Diffuse / batwing / 1119mm

62317

Design: O/M
LED light source with good colour consistency and
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



- Structure**

 - 1 Profile
 - 2 End caps
 - 3 Fitting accessories
 - 4 Profile coupling
- Diffuser**

 - A Polycarbonate frost diffuser

Light Source

 - B LED Modules

| LED | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-------------|
| Power | | 27+20W | 32,9+24,4W |
| Flux | | 5200+2360lm | 2440+1480lm |
| Efficiency | | 161lm/W | 68lm/W |
| LOR | | - | 52% |
| UGR | | - | <25 |



Beam angle
Diffuse / batwing

Application



Weight
0,5Kg



Finishes

Choose the length and layout of the system exactly as you want it, to model the right lighting functions for different tasks. For further information please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class C
and E
Model Identifier WU-M-594-840, 89603217

