

34+20W / 3300+1480lm / 4000K / DALI /
Diffuse / batwing / 1399mm

62327

Design: O/M

LED light source with good colour consistency and
long operation lifespan.LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz**Structure**

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling


DiffuserA Polycarbonate frost
diffuser**Light Source**

B LED Modules

LED	4000K	Light Source	Luminaire
Power		34+20W	40+24,4W
Flux		6500+2360lm	3300+1480lm
Efficiency		164lm/W	74lm/W
LOR		-	54%
UGR		-	<25

Beam angle
Diffuse / batwing

Application

Weight
0,6Kg**Finishes**For the specific supply of "DALI 2" drivers, please contact:
support@om-light.comChoose the length and layout of the system exactly as you want it, to
model the right lighting functions for different tasks. For further
information please contact: support@om-light.com**Data according to regulations**2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class C
and E

Model Identifier 89603212, 89603217, WU-M-594-840