

## MGB Pendant indirect

45W / 2300lm / 4000K / DALI / Diffuse  
indirect / 1560mm

62350



Design: Eduardo Souto de Moura

Pendant luminaire with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser with user friendly clipping system.

Steel end caps with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser for direct light and indirect light.

Fitting accessories ordered Separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



| LED 4000K  | Light Source | Luminaire |
|------------|--------------|-----------|
| Power      | 45W          | 65W       |
| Flux       | 5750lm       | 2300lm    |
| Efficiency | 128lm/W      | 35lm/W    |
| LOR        | -            | 40%       |
| UGR        | -            | <25       |



Beam angle  
Diffuse indirect

Application



Weight  
7Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

Mandatory

56051 Clear base DALI

Ø60x35mm

54081 Aluminium base DALI

Ø60x37mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com